



# DUMPSTODAY

## Salesforce

**CRT-600 Exam**

Javascript Developer I

# Questions & Answers

(Demo Version - Limited Content)

Thank you for Downloading CRT-600 exam PDF Demo

Get Full File:

<https://dumpstoday.com/crt-600-dumps/>

**WWW.DUMPSTODAY.COM**

# Version: 11.0

---

## Question: 1

---

Refer to the code below:

```
01 const exec = (item, delay) =>{
02 new Promise(resolve => setTimeout( () => resolve(item), delay)),
03 async function runParallel() {
04 Const (result1, result2, result3) = await Promise.all{
05 [exec ('x', '100') , exec('y', 500), exec('z', '100')]
06 };
07 return `parallel is done: ${result1} ${result2}${result3}`;
08 }
}
```

Which two statements correctly execute the runParallel () function?

Choose 2 answers

- A. Async runParallel () .then(data);
- B. runParallel ( ) .done(function(data){  
return data;  
});
- C. runParallel () .then(data);
- D. runParallel () .then(function(data)  
return data

---

**Answer: B, D**

---

Explanation:

---

## Question: 2

---

A developer needs to test this function:

```
01 const sum3 = (arr) => (
02 if (!arr.length) return 0,
03 if (arr.length === 1) return arr[0],
04 if (arr.length === 2) return arr[0] + arr[1],
05 return arr[0] + arr[1] + arr[2],
06 );
```

Which two assert statements are valid tests for the function?

Choose 2 answers

- A. `console.assert(sum3(1, '2') == 12);`
- B. `console.assert(sum3(0) == 0);`
- C. `console.assert(sum3(-3, 2) == -1);`
- D. `console.assert(sum3('hello', 2, 3, 4) === NaN);`

---

**Answer: A, C**

---

Explanation:

---

### Question: 3

---

Which statement phrases successfully?

- A. `JSON.parse('foo');`
- B. `JSON.parse("foo");`
- C. `JSON.parse('foo');`
- D. `JSON.parse("foo");`

---

**Answer: D**

---

Explanation:

---

### Question: 4

---

Refer to the code below:

```
01 let car1 = new promise( (_, reject) =>
02   setTimeout(reject, 2000, "Car 1 crashed in"));
03 let car2 = new Promise(resolve => setTimeout(resolve, 1500, "Car 2
04   completed"));
05 let car3 = new Promise(resolve => setTimeout(resolve, 3000, "Car 3
06   Completed"));
07 Promise.race([car1, car2, car3])
08   .then(value => {
09     let result = $(value) the race. `;
10   })
11   .catch( err => {
12     console.log("Race is cancelled.", err);
13   });
```

What is the value of result when Promise.race executes?

- A. Car 3 completed the race.
- B. Car 1 crashed in the race.
- C. Car 2 completed the race.
- D. Race is cancelled.

---

**Answer: C**

---

Explanation:

---

**Question: 5**

---

Refer to the code below:

```
for(let number =2 ; number <= 5 ; number += 1 ) {  
  // insert code statement here  
}
```

The developer needs to insert a code statement in the location shown. The code statement has these requirements:

1. Does require an import
2. Logs an error when the boolean statement evaluates to false
3. Works in both the browser and Node.js

Which meet the requirements?

- A. `assert (number % 2 === 0);`
- B. `console.error(number % 2 === 0);`
- C. `console.debug(number % 2 === 0);`
- D. `console.assert(number % 2 === 0);`

---

**Answer: B**

---

Explanation:

**Thank You for trying CRT-600 PDF Demo**

<https://dumpstoday.com/crt-600-dumps/>

**Start Your CRT-600 Preparation**

*[Limited Time Offer]* Use Coupon "**SAVE20**" for extra 20% discount the purchase of PDF file. Test your CRT-600 preparation with actual exam questions